

MAINTENANCE OF RESIN FLOORS



Product Data Sheet

Data Sheet Ref: CLNG 11/03 Page 1

RECOMMENDATIONS for CLEANING:

Having invested in a high quality flooring system, such as a resin coating or screed, it is essential that a regular cleaning regime is adopted. This will not only enhance the appearance and life of the floor finish by removing dirt and contamination, but will also ensure that floors are kept safe and hygienic and free from slip hazards.

Designer Resin Floors Ltd has a range of maintenance cleaning products specifically for resin floor finishes. Formulated using natural derived and ecologically sound material, the range of products contains no caustic alkalis, harmful solvents, phosphates, silicates or aggressive biocides. They are safe in use and have a superior environmental profile.

FREQUENCY:

Cleaning should be carried out on a regular basis, frequency will largely depend on the type of contamination and level of cleanliness required. For maximum effectiveness, cleaning should be carried out on a daily or weekly basis as part of standard housekeeping procedures.

THE PRODUCT: INDUSTRIAL FLOOR CLEANER

A versatile aqueous industrial floor cleaner and degreaser. Its powerful cleaning action effortlessly removes most types of soiling including greases, grime, oils and hydrocarbons. Industrial Floor Cleaner leaves no smear or residue upon rinsing. Suitable for use with non-abrasive manual systems with cold or warm water OR with non-abrasive floor scrubber/drying machines.

DILUTION RATE: 1:20 to 1:50

ESTIMATED COVER: 50m² to 250m²
(per litre)

MAINTENANCE CLEANING:

This system is designed for regular maintenance as part of standard housekeeping

PREPARATION

1. Where possible, move portable equipment/machinery to one side to leave a clear unobstructed floor areas.
2. Sweep floor to remove loose material and surface debris.

MAINTENANCE CLEANING:

1. To a Combination floor scrubber/dryer machine, attach red pads or stiff nylon brushes and carefully add a 2% solution (1:50) or Industrial Floor Cleaner to the machine tank.
2. Use the floor scrubber/dryer machine and simultaneously scrub the floor and wet vacuum the soiled water into the recovery tank.
3. For heavy soiled floors make the first pass of the machine without using the vacuum facility, this leaves the product in contact with the dirt longer and aids removal. On the second pass, scrub the floor and recover soiling as normal.
4. Depending on the floor area, it may be necessary to change the red pad during this operation.
5. Alternatively, dilute Industrial Floor Cleaner at a rate of 1:20-50 with warm water in a mop bucket.
6. Apply solution generously to small section of the floor with a mop, used in a figure eight motion, repeat until floor area has been completely covered.
7. Rinse thoroughly with clean warm water.

OTHER PRODUCTS for the maintenance of resin floors:

Oil Remover	PVC Tape Remover
Tyre Mark Remover	HD Tyre Mark Remover
Fat & Grease Remover	Chewing Gum Remover
Machine Cleaner	Tool Cleaner